

## IRRIGATION LEGEND

PRODUCT DESCRIPTION

HUNTER I-20-04-XX/I-20-06-XX NOZZLE AS SHOWN NOZZLE PERFORMANCE:

#3.5 @ 40 PSI - 3.0 GPM 38' RADIUS #6 @ 40 PSI - 4.9 GPM 40' RADIUS #8 @ 40 PSI - 6.0 GPM 41' RADIUS #10 @ 40 PSI - 8.4 GPM 42' RADIUS

HUNTER ICV/IBV ELECTRIC CONTROL VALVE SIZED AS SHOWN

HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR WATER METER MINIMUM SIZE @ 75 GPM IS 2.0"
BACKFLOW PREVENTER SIZED TO SYSTEM GPM HUNTER HQ-44-XX-AW QUICK COUPLER VALVE (OPTIONAL)
HUNTER IC-1200 SOLID STATE METAL CABINET CONTROLLER

### IRRIGATION NOTES

- SPRINKLER LOCATIONS ARE TO SCALE
   PIPE LOCATIONS ARE DIAGRAMMATIC
   ALL SPRINKLERS TO BE INSTALLED ON .75" SCH 80 SWING JOINTS 4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS RECOMMENDATIONS
- 5. MAINLINE DEPTH TO BE NO LESS THAN 18"
  6. LATERAL DEPTH TO BE NO LESS THAN 16"
  7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX B. LOCATE VALVES/QCVS OUT OF HIGH TRAFFIC AREAS
  9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF

- 10. OCV TO BE LOCATED IN 10" VALVE BOX 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM 12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE, FEDERAL CODES
- 13. REFER TO HUNTER INSTALLATION DETAILS
  14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS
  15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
  16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

# SYSTEM PERFORMANCE DATA

## SIZE

ZONE A1 A2 A3 A4 A6 A6 A7 A7 A10

OFFICIAL BASEBALL FIELD

I-20 SIX ROW DESIGN

Hunter Industries Hunter Industries 1940 Diamond Street San Marcos, Callfornia 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com

Hunder Industries offers this plan as a general guide for estimating purposes and offers no Indennity, expressed or Implied, for projects installed from this plan. Because of the many variables of every system and of every site we recommend that a qualified Irrigation designer be consulted.

SHEET 유 1