



IRRIGATION LEGEND

PRODUCT DESCRIPTION
HUNTER I-40-04-SS-B-XXI-40-06-SS-B-XX, NOZZLE AS SHOWN
HUNTER I-40-04-SS-B-XXI-40-06-SS-B-XX, NOZZLE AS SHOWN

NOZZLE PERFORMANCE: #10 @ 5.0 Bars - 46.8 I/min 15.8m RADIUS

⊕ HUNTER ICV/IBV ELECTRIC CONTROL VALVE SIZE AS SHOWN

⊕ HUNTER HQ-44-XX-AW QUICK COUPLER VALVE (OPTIONAL)

② HUNTER HQ-600-M SOLID STATE METAL CABINET CONTROLLER

BE HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR

BE HUNTER SELECTION

BACKFLOW PREVENTER SIZED TO SYSTEM I/min

MANILINE PIPE

LATERAL PIPE

SLEETING

ISOLATION VALVE LINE SIZED

- **IRRIGATION NOTES**
- HUNTER FLOW SENSOR IN LINE SIZED FLOW CLIK TEE "FCT"

- SPRINKLER LOCATIONS ARE TO SCALE
 PIPE LOCATIONS ARE DIAGRAMMATIC
 ALL SPRINKLERS TO BE INSTALLED ON 32mm SCH 80 SWING JOINTS
- 4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS RECOMMENDATIONS

- 5. MAINLINE DEPTH TO BE NO LESS THAN 460mm
 6. LATERAL DEPTH TO BE NO LESS THAN 100mm
 7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX
 8. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS
 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
 10. QCV TO BE LOCATED IN 10" VALVE BOX
 11. ALL SLEVES TO BE ZX PIPE RUN THROUGH THEM
 12. INSTALL ALL CONDES
 13. REFER TO HUNTER INSTALLATION DETAILS
 14. REFER TO HUNTER CATALOG FOR PERFORMANCE
 15. REPERFORMANCE
 16. CONDENSES TO DEPTAIN THE VALVE
 17. REPERFORMANCE
 18. REPERFORMA
- 15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
 16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

WATER REQUIREMENTS

WATER REQUIREMENT AT
-FIELD ELEVATION
-WITHIN 30m OF FIELD
-DOWNSTREAM OF
BACKFLOW
IS 186 l/min @ 5.54 Bars

VALVE ID GUIDE

STATION NUMBER

PRECIPITATION RATE mm/hr

A2 A1	ZONE	SYS
o	SIZE	M
11.2 5.6	Ę	찙
93	Š	8
45.9 23.2	공	RM/
88	2	Ź
1.2 1.2	SC(10% WINDOW)	E DATA

CROQUET COURT

I-40 DESIGN

SHEET <u>~</u> 유