


VALVE IDENTIFICATION GUIDE

SYMBOL	MANUFACTURER/MODEL/DESCRIPTION	QTY
	Hunter I-CV-G 50mm 25 mm, 40 mm, 50 mm, and 80 mm Plastic Electric Remote Control Valves, Globe Configuration, with NPT Threaded Inlet/Outlet, for Commercial/Municipal Use.	10
	Watts 919QT 50mm Backflow reduced pressure zone	1
	Water Meter 50mm	1
	Irrigation Lateral Line: PVC Class 200 SDR 21	233.3 m
	Irrigation Lateral Line: PVC Class 200 SDR 21 40	247.0 m
	Irrigation Lateral Line: PVC Class 200 SDR 21 50	138.8 m
	Irrigation Lateral Line: PVC Class 200 SDR 21 80	83.3 m
	Irrigation Mainline: PVC Schedule 40 80	49.1 m
	Irrigation Mainline: PVC Schedule 40 100	68.7 m



IRRIGATION LEGEND

Scale: 1:400

SYMBOL	MANUFACTURER/MODEL/DESCRIPTION	QTY	kPa	l/min
	Hunter I-50-06-SS Turf Rotor, 15 cm Pop-Up. Adjustable to Full Circle. Drain Check Valve, Stainless Steel Riser, 25 mm Female NPT Inlet Threads, Standard Nozzle.	16	551.6	104.9
	Hunter I-50-06-SS-ON Turf Rotor, 15 cm Pop-Up. Adjustable to Full Circle. Drain Check Valve, Stainless Steel Riser, 25 mm Female NPT Inlet Threads, Dual Opposing Nozzle.	8	551.6	117.0

Hunter Industries offers this plan as a general guide for estimating purposes and offers no indemnity, expressed or implied, for projects installed from this plan. Consult a qualified irrigation designer to account for system and site variables.

TECHNICAL ASSISTANCE
1-800-319-4796
WWW.HUNTERINDUSTRIES.COM

SOCCER FIELD - 91 X 60

XX
XX MAIN LINE LAYOUT



HUNTER INDUSTRIES
1940 DIAMOND STREET
SAN MARCOS, CALIFORNIA 92078

SHEET
1 of 2